This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter may be used in a stock machine, with no modifications required. However, if any modifications have been made, tuning/jetting adjustments may be required. The following procedure MUST be followed to ensure a proper fit and seal of the K&N Filtercharger®.

## **INSTALLATION**

- 1) Remove the stock air filter according to the owners manual.
- 2) Clean the inside of the air box where the filter seals.
- 3) Remove the backing from the supplied gasket.
- 4) Install gasket in the air box where the filter will seal.
- 5) Install the K&N Filtercharger®.

## THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE **ENGINE COULD RESULT.**

• 1455 CITRUS ST., P.O. BOX 1329, RIVERSIDE, CA., U.S.A. 92502 • TECH SERVICE 800-858-3333 • FAX 951-684-9060 • e-mail: tech@knfilters.com • WWW: http://www.knfilters.com

17211a 6/8/05



## INSTALLATION INSTRUCTIONS Part Number KA-1600

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter may be used in a stock machine, with no modifications required. However, if any modifications have been made, tuning/jetting adjustments may be required. The following procedure MUST be followed to ensure a proper fit and seal of the K&N Filtercharger®.

## INSTALLATION

- 1) Remove the stock air filter according to the owners manual.
- Clean the inside of the air box where the filter seals. 2)
- Remove the backing from the supplied gasket. 3)
- 4) Install gasket in the air box where the filter will seal.
- 5) Install the K&N Filtercharger®.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SERVICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE **ENGINE COULD RESULT.**