

This filter fits: SEE CATALOG FOR CURRENT APPLICATIONS

Congratulations, you have purchased the finest air filter that money can buy. With proper care, this filter will last 1 million miles or more. This filter can be used in a stock machine, with no modifications required. If any engine modifications have been made tuning/jetting adjustments may be required. There are special installation instructions, so please follow the procedures outlined below to ensure that the K&N Filtercharger® seals properly.

- 1. Remove the stock filter.
- 2. Carefully clean the inside of the air box.
- 3. Gently work the smaller folded part of the filter into the sealing groove until it properly seats. (Fig. 1)
- 4. Bend your K&N air filter as shown. (Fig. 1)
- 5. Install the front face and rear corners of the K&N air filter into the sealing grooves. (Fig. 2)
- 6. For correct installation, please reference (Fig. 3)
- 7. Replace your original air box cover.

NOTE: When removing filter for servicing, DO NOT PULL FILTER FROM ABOVE BEND LINE. Remove as shown in Figure 4.

THESE INSTRUCTIONS MUST BE FOLLOWED EVERY TIME THE FILTER IS SER-VICED, OTHERWISE THE FILTER MAY NOT SEAL, AND DAMAGE TO THE ENGINE COULD RESULT.



Fig. 1




Fig. 3



Fig. 2



Fig. 4